

Multiple materials

Equipped with multiple built-in printing modes, it supports clear printing on various materials such as cable sleeves, labels, heat-shrink tubes, and terminal marker strips.

Power-off recovery

Automatic memory function that automatically saves edited content. When the device is turned off or experiences an unexpected power outage, you can choose to restore the content edited before shutdown.

Intelligent design

Enable automatic half-cutting and automatic full-cutting.

High quality print head

It uses a Japanese Kyocera print head, which is durable and provides clear printing.



CP 819 Configuration and Technical Parameters

Printing method Thermal transfer

Resolution 300dpi

Ribbon color black/red/white

Label color yellow/white/silver

Consumable type cable tube/label/heat shrink tube

Label specifications 6mm \ 9mm \ 12mm

Cable tube specifications 0.5mm²~10mm²

Heat shrink tube specifications φ1.0mm~φ6.0mm

Section length setting 6~100mm

Repeat times 1~200 times

Printing speed 45 segments/min (half-cut, 20mm segment length)

Show LED white backlight two-segment content display

Input Chinese(Or other customized languages)/English/electrical symbols

Storage capacity 100 files

Cutting method automatic half/full cut

Keyboard 85-key standard keyboard

Power supply 12V-3A

Dimensions 325mm×270mm×90mm

Weight 3kg

Work environment Temperature 5℃-35℃, humidity 15%-80% RH

CP 819 Application scenarios









ZOTA Co., Ltd.